

**CARBON DIOXIDE (CO₂) DRY REFORMING OF GLYCEROL FOR
SYNGAS PRODUCTION OVER RHENIUM PROMOTED ON Ni-BASED
CATALYST SUPPORTED ON SANTA BARBARA AMORPHOUS 15 (SBA15)**

JESSY LYNN JASPIN

SUPERVISOR : DR SUMAIYA BINTI ZAINAL ABIDIN @ MURAD

BACHELOR OF CHEMICAL ENGINEERING

UNIVERSITI MALAYSIA PAHANG

2017

ACKNOWLEDGEMENTS

I am grateful to the God for the good health and wellbeing that were necessary to complete this thesis.

I wish to express my sincere thanks to my supervisor, Dr Sumaiya Binti Zainal Abidin @ Murad for the continuous encouragement, patience and advices who I am extremely thankful and indebted to her for correcting my mistake in the completion of this thesis and valuable guidance extended to me.

Moreover, I take this opportunity to express gratitude to all the staffs of Faculty of Chemical Engineering and Natural Resources laboratory for giving me cooperation and permission throughout the experiments being conducted. Besides, I am so grateful to my senior, Nur Nabillah Binti Mohd Arif who always guided and support me to finish this experiment as well as my friends, Hasan Bin Shahul Hamid, Nurul Syafiqah Binti Rosli and Norazuwen Binti Rusli who always encouraging me to never give up for my future.

Lastly, my sincere thankful and grateful goes to my beloved parents, Jaspin Bin Kwan and Suaning Binti Sinsan, my siblings, Sharon Lynn Jaspin, Jacqueline Jaspin, Steward Owen Jaspin and Vanessa Lynn Jaspin who were always encourage me with their prayers and guided me with their love and faith so I can be one of the degree holder in Bachelor of Chemical Engineering.

TABLE OF CONTENT

ABSTRAK.....	7
ABSTRACT.....	8
CHAPTER 1	9
INTRODUCTION	9
1.1 Background of the study	9
1.2 Motivation	11
1.3 Problem statement	11
1.4 Objectives.....	11
1.5 Scopes of study.....	12
CHAPTER 2	13
LITERATURE REVIEW	13
2.1 Energy	13
2.2 Fossil Fuels.....	13
2.3 Synthesis Gas	14
2.4 Glycerol as the by-product of biodiesel process	14
2.5 Process for Glycerol dry reforming into syngas.....	15
2.5.1 Glycerol steam reforming	16
2.5.2 Partial Oxidation.....	17
2.5.3 Pyrolysis	17
2.5.4 Glycerol dry Reforming.....	18
2.6 Catalyst.....	19
2.6.1 Based catalyst	19
2.6.2 Catalyst Support	19
2.6.3 Promoter of catalyst.....	20
CHAPTER 3	22
METHODOLOGY	22
3.1 Chemicals	22
3.2 Catalyst Characterization	22
3.2.1 Scanning Electron Microscopy (SEM).....	22
3.2.2 X-Ray Diffraction (XRD).....	22
3.2.3 Brunauer-Emmett-Teller (BET) multipoint.....	23
3.2.4 Thermogravimetric (TGA)	23

3.2.5 Field Emission Scanning Electron Microscope (FESEM)	24
3.3 Dry Reforming Experimental Work.....	24
CHAPTER 4	26
RESULTS AND DISCUSSION	26
4.1 Introduction	26
4.2 Physicochemical Characterization of 3%Re_Ni/SBA15 and Ni/SBA15 catalyst	26
Chapter 5	32
Effect of Reaction Parameters towards Glycerol Dry Reforming	32
5.1 Introduction	32
5.2 The effect of carbon to glycerol ratio (CGR)	32
5.3 The effect of temperature at fixed CGR:1	35
5.4 The comparison of Ni/SBA15 and 3%Ni/SBA15 catalyst.....	38
CHAPTER 6	43
CONCLUSION	43
6.1 Conclusion.....	43
REFERENCE.....	46

LIST OF TABLES

Table 4.1 Crystallite diameter for Ni/SBA-15 from XRD analysis	27
Table 4.2 Crystallite diameter for 3%Re_Ni/SBA-15 from XRD analysis	27
Table 4.3 BET Surface area for Ni/SBA-15 and 3%Re_Ni/SBA-15 catalyst	28
Table 5.1 Glycerol conversion of 3%Re_Ni/SBA-15 at different range of temperature	36
Table 5.2 Hydrogen yield of 3%Re_Ni/SBA-15 catalyst at different range of temperature	36

LIST OF FIGURES

Figure 1.1. Present world syngas market	10
Figure 3.1 Experiment setup for the glycerol dry reforming	25
Figure 4.1 XRD pattern of Ni/SBA-15 and 3%Re_Ni/SBA-15 where (A)NiO	27
Figure 4.2 Morphology structure of Ni/SBA-15 at 5000x magnification	29
Figure 4.3 Morphology structure of 3%Re_Ni/SBA-15 catalyst at 5000x magnification	30
Figure 4.4 TGA analysis of Ni/SBA-15 and 3%Re_Ni/SBA-15 at 10 kmol^{-1} from 30°C to 900°C	31
Figure 5.1 The glycerol conversion of 3%Re_Ni/SBA-15 at different CGR	33
Figure 5.2 The trend of different CGR versus glycerol conversion	34
Figure 5.3 The hydrogen yield of 3%Re_Ni/SBA-15 at different CGR	34
Figure 5.4 The trend of different CGR versus hydrogen yield	35
Figure 5.5 The glycerol conversion of 3%Re_Ni/SBA-15 at different range of temperature	36
Figure 5.6 The trend of glycerol conversion of 3%Re_Ni/SBA-15 at different range of temperature	37
Figure 5.7 The hydrogen yield of 3%Re_Ni/SBA-15 at different range of temperature	37
Figure 5.8 The trend of hydrogen yield of 3%Re_Ni/SBA-15 at different range of temperature	38
Figure 5.9 The glycerol conversion of Ni/SBA-15 and 3%Re_Ni/SBA-15 catalyst	39
Figure 5.9 The glycerol conversion of Ni/SBA-15 and 3%Re_Ni/SBA-15 catalyst	39
Figure 5.10 The hydrogen yield of Ni/SBA-15 and 3%Re_Ni/SBA-15 catalyst	41
Figure 5.11 FESEM image of spent Re-promoted Ni/SBA-15 catalyst at 2000x magnification	41
Figure 5.11 FESEM image of fresh Re-promoted Ni/SBA-15 catalyst at 2000x magnification	42
Figure 5.13 TPO curve for the spent catalyst of 3%Re_Ni/SBA-15 at 10 kmol^{-1} from 25°C to 900°C	42